



Q_K (l/min)	4	6	8	10	12	16	20										
y	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17

Type code		Displacement cm ³ /rev	Dimensions					Weight Kg
			A	B	L	d	g	
PRD2-264Dy/l	PRD2-264Sy/l	11	54	97	118	20	M8x1.25	3.9
PRD2-264Dy	PRD2-264Sy	11	48.54	97	118	20	M6	3.9
PRD2-265Dy/l	PRD2-265Sy/l	14	49	102	123	20	M8x1.25	4.1
PRD2-265Dy	PRD2-265Sy	14	49	102	123	20	M6	4.1
PRD2-266Dy/l	PRD2-266Sy/l	16	54	105	126	20	M8x1.25	4.3
PRD2-266Dy	PRD2-266Sy	16	49	105	126	20	M6	4.3
PRD2-267Dy/l	PRD2-267Sy/l	19	49	110	131	20	M8x1.25	4.5
PRD2-267Dy	PRD2-267Sy	19	49	110	131	20	M6	4.5
PRD2-268Dy/l	PRD2-268Sy/l	22.5	56.64	116	137	20	M8x1.25	4.7
PRD2-268Dy	PRD2-268Sy	22.5	56.64	116	137	20	M6	4.7
PRD2-269Dy/l	PRD2-269Sy/l	26	60	122	149	22	M8x1.25	4.9
PRD2-269Dy	PRD2-269Sy	26	60	122	149	22	M6	4.9